

## THS 4 | THS 5



Figure: THS 4

The model THS 5 is mechanically operated and powered by an hydraulic control valve.



### New model for residential use and dependable quality

Home-owners who have a fire-place are confronted with the choice of either burning rather expensive commercial firewood or splitting their own logs at home using a log-splitter. BGU mini log splitters are tiny, user-friendly, very affordable machines that still comply with effective power and quality requirements. No large storage rooms and no technical skills or expertise are required for operating one of these splitters.

- user-friendly, two-hands safety control
- On/off switch operation (THS 4)
- Highly performant electric motor
- Highly performant electric motor
- maintenance free
- Compact design and construction
- Rubber grips and castor wheels for easy handling

Technical data	THS 4	THS 5
Electric motor drive	1,5 kW P <sub>1</sub>	1,5 kW P <sub>1</sub>
Voltage	230 V	230 V
Splitting force	4 t	5 t
Log capacity	max. 350 mm	max. 530 mm
Dimensions (W x H x L)	810 x 480 x 360 mm	1150 x 480 x 360 mm
Weight	approx. 47 kg	approx. 54 kg
Code no.	90264	90265

## Spessart Woody HS 7



### A special model for a very attractive price!

- 4-ways wedge is included
- Stepless easy stroke adjustment by means of a rear adjustment rod
- Noise-less, very powerful electric motor (high power at low 1450 RPM)
- Manual setting of the table for splitting long logs (no other implements are required to remove the table)



Full cord log length can be easily handled on this machine by simply removing (flip over and then unhook) or sliding the intermediate table all the way down. In this asset, the machine is capable of handling logs of any kind of wood up to 1.08 m length. The figure shows an HS 75/3.

Technical data	Spessart Woody HS 7 (400 V)	Spessart Woody HS 7 (230 V)
Electric motor drive	3,0 kW P <sub>1</sub>	2,2 kW P <sub>1</sub>
Splitting force	7 t	7 t
Voltage	400 V 16A CE-connector	230 V
Ram stroke	520 mm	520 mm
Splitting capacity	550 / 750 / 1080 mm	550 / 750 / 1080 mm
Total height, retracted pos.	1100 mm	1100 mm
Total height, extended pos.	1600 mm	1600 mm
Dimensions (W x L)	500 x 750 mm	500 x 750 mm
Weight	approx. 126 kg	approx. 126 kg
Code no.	90274	90277