



STAALMEESTER™

PRODUCTIVITY, COST EFFICIENCY & SERVICE TO THE FARMER

Teagle Spiromix

Tractor Mounted Concrete Mixers

Teagle





- Easy Loading through the wide mouth of the drum.
- Easy Unloading - the drum rotates in one direction for mixing and in the opposite direction for unloading.
- Hydraulic motor drive - easily controlled from the tractor seat via the external services spool valve.
- Good Mix - the deep spirals, needed to give a good unloading action, also give a quick and thorough mix.
- Good Unloading Height - because the drum does not tip to unload, the discharge height is always good.

Model	100H	200H
Minimum tractor size	15kW / 20HP	40kW / 50HP
Linkage	Cat 1/2	Cat 2
Drum Volume	280 litres (10 cu.ft.)	560 litres (20 cu.ft.)
Approx. Mix Volume	140 litres (5 cu.ft.)	280 litres (10 cu.ft.)
Loading Height to Drum Lip	37 cm (15 in)	57cm (22 in)
Weight Empty	118 kg (262 lb)	190 kg (420 lb)
Approx. Laden Weight	430 kg (950 lb)	815 kg (1790 lb)
Drum Diameter	65 cm (25 in)	82 cm (32 in)
Height Overall with machine on ground	89 cm (35 in)	111 cm (43 in)

For fast and convenient mixing of concrete and other material on the farm.

* Working heights will increase by up to 1 m [3' 3"] depending on tractor
 ** Typical size to provide adequate lifting capacity and stability.

The company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice.