

PRODUCTIVITY, COST EFFICIENCY & SERVICE TO THE FARMER

## Enorossi Fertilizer Spreaders



## **Accessories**



Side Conveyor



**Double Conveyor** 



**Articulated Agitator** 



Stainless steel fans and disc



**Version with PVC hopper** 

## **Standard equipment**

Three point hitch, cat. I and II, Maximum spreading width 12-18 meters depending the fertilizer,
Oil bath gear box,
Double lever command, indipendent opening and closing right/left,
PTO 540 rpm,
Agitator,
4 fans,
PTO shaft (1" 3/8 Z6 tractor side yoke),
On request we can supply the

tank Inox or Galvanized, The 500 liters it is possible to have it in PVC.

## Steel or polyutherane.

Fertilizer spreaders are used for applying granular fertilizers and pesticides to turf.

In order to guarantee a perfect descending of the product, the Enorossi SPF series spreaders are equipped with a pressed steel hopper in one piece. It is possible to intervene with the distribution of the product for obtaining a localized or uniform spreading.

**INCLUDED:** Articulated agitator.

SPF Series with cardan. SPF-400 available with PVC and galvanized hopper.

Model	Spreading width	Weight	Max Load
SPF-250	600-1800 cm / 20-59 ft.	53 kg	300 kg
SPF-300	600-1800 cm / 20-59 ft.	55 kg	350 kg
SPF-400	600-1800 cm / 20-59 ft.	57 kg	450 kg
SPF-500	600-1800 cm / 20-59 ft.	59 kg	550 kg