



STAALMEESTER™

PRODUCTIVITY, COST EFFICIENCY & SERVICE TO THE FARMER

6776 Harvester Hammer mill



Much experience and meticulous development has produced this superbly engineered choice of three versatile combinations, to this day progressively developed and refined, they remain the standard throughout the Southern hemisphere by which hammer mill combinations are judged.



The harvester head is bolted to the mill. Unscrew it and you have the ordinary mill grinder. Crops that grow in rows such as maize, sorghum, sunflower, etc. can be processed rapidly. The robust maize head makes the crop flow evenly into the machine with the minimum of wear and consequently less maintenance.

Simplicity is the key note.

A single rotor axle with a spiral takes up the plant and passes it back to two beaters which deposit it into the hopper of the mill.



An additional beater easily handles material with a high moisture content and makes sure that material is presented correctly to the feeding tray, and by means of the auger it is fed evenly through to the rotor housing.

The complete flywheel can be removed from the machine in 10 minutes.

The milled material can be collected in bags on a platform or tossed into a trailer by means of a discharge chute.

Specifications:

Auger speed 580 r/pm
 PTO power ** 40 - 70 kW
 Cyclone 2 to 4 outlets
 Discharge chute Yes

**The recommended tractor size depends on the working conditions, growth and environmental factors.



No Gears or Chains

Please note : We offer demonstration facilities for all our products, so please do not hesitate to ask us for a demonstration. We want to prove that we are no. 1 in the agricultural sector..

