



**STAALMEESTER™**

PRODUCTIVITY, COST EFFICIENCY & SERVICE TO THE FARMER

## Enorossi Sickle Bar Mower



The high speed cutting systems ensure a clean cut of the product. The sickle bar mowers have an allowable cut from  $-45^{\circ}$  to  $+90^{\circ}$ , respect to the horizontal plan, to allow the mowing of hedges, ditches, banks, etc. The double action cutter bar ensures a sharp clean cut on any type of grass. Three Point Hitch with double action cutter bar. All bars are equipped with automatic safety release to protect the bar from any obstacles. The compactness of the sickle bar mower allows working with low-power tractors ensuring money savings as well as productivity.

Standard production equipment: cardan shaft, spare blade and blade protection.



**Ideal for small farms.  
Built to adapt to any type of land....**



BFS version: bolted guards.



Breakaway system.



Forged support.



High resistant swivel-  
ling arms.

## TECHNICAL SPECIFICATIONS :

- Frame and 3 point hitch made of FE 510 steel.
- Transmission via three groove pulleys made of spheroidal cast iron with n. 3 belts.
- Drive shaft made of tempered and highly resistant 39NiCrMo3.
- Self-sharpening blade having riveted sections made of high quality steel.
- External shoe made of spheroidal cast iron.
- Main cutter bar made of 55Si7 to ensure high resistance and optimal flexibility.
- Automatic safety release to protect the bar from any obstacles.
- 1080 movements at 540 rpm. Breakaway system.
- Forged support.
- Cuts at 90° up and 75° down.
- High quality powder-coat paint.
- BFS equipped with bolted guards.
- Heavy duty shielded PTO shaft.

**Key features :** The double action cutter bar ensures a sharp clean cut on any type of grass. The safety breakaway bar helps protect the cutter from obstructions in the field.

Design and/or specifications are subject to change without prior notification.



External shoe made of spheroidal cast iron plus swath board.



Enorossi Sickle Bar Mower in transport position.



Compact 3 point hitch designed for small tractors.

## Available in 3 models..

Model	BFS 165	BFS 180	BFS 210
Cutting Action	Double	Double	Double
Lift	Mechanical or Hydraulic	Mechanical or Hydraulic	Mechanical or Hydraulic
HP	20 - 75	30 - 75	30 - 75
Working width (cm)	165	180	210
Weight (kg)	263	271	287

If you are viewing this brochure electronically, you can go directly to demo videos on our website here:

[View the Enorossi Sickle Bar Mower demo video here](#)

Design and/or specifications are subject to change without prior notification.