



STAALMEESTER™

PRODUCTIVITY, COST EFFICIENCY & SERVICE TO THE FARMER

Enorossi Bat Rakes

AGRICULTURAL MACHINERY
enorossi

Dreaming with us



BATRAKE®

Carted V-Rake

Available in 8, 10, 12 wheel sizes.

Enoagricola Rossi now offers the latest innovation in High Capacity Caddy rakes with the BATRAKE. The heavy 7 mm spring tines provide for excellent wear and strong resistance to breakage.

Go from a V rake configuration to single side without leaving the tractor seat.

The BATRAKE's unique lifting system gives you the ability to only partially raise the V-rake when coming to the end of the field, rather than into the full transport position. A single hydraulic hose allows it to be used on older tractors with limited hydraulic remotes. Windrows width from 3' to 7'.

This unique V-rake combines attention to detail and quality of the work performed. The Batrake's raking wheels can be considered among the best on the market with 32 inc. of ground clearance!

Central raking wheel with hydraulic lift, hydraulic raking angle control and road homologation available upon request.





Adjustable pressure spring.



Single hydraulic hose.



Optional hydraulically raised Kicker wheel available for all sizes.



Patented pressure variable springs on the single wheel configuration keep ideal pressure on each raking wheels at all times.



Transport position.

Enorossi 8, 10, or 12 Wheel Bat Rake with standard central raking wheel...

Design and/or specifications are subject to change without prior notification.

TECHNICAL SPECIFICATIONS :

- Optional hydraulically raised kicker wheel available for all sizes.
- Frames made of FE 510 steel.
- High quality powder-coat paint.
- Adjustable pressure spring. Single hydraulic hose.
- Patented pressure variable springs on the single wheel configuration keep ideal pressure on each raking wheels at all times.
- Heavy tubular frame with strategically placed bracing
- Lateral frame sections 100 mm. x 80 mm., 4 mm. thickness.
- Pull bar sections 150 mm. x 80 mm., 4 mm.thickness.
- Raking wheels made of C85 heat tempered steel to ensure stability and durability over time.
- Raking wheels Ø 140 cm., central flange Ø 3,5 mm., n° 40 wheel tines Ø 6,9 mm.
- 205.70/15 transport tires.
- Molded steel hubs with tapered roller bearings.
- Rake wheel arms with torsion spring to adjust the ground pressure.
- Hydraulic cylinders with simple effect for lifting side frames.
- Raking wheels sit at a 7° to create fluffier windrows and leave less hay in your fields.
- Windrow width adjustment by using mechanical tensioners or hydraulic cylinders upon request.
- Independent rake wheel arms to follow all ground contours.
- Possibility to operate just one side, without adding any additional kit.
- Hydraulic kicker wheel with N° 1 raking wheel, Ø 110 cm.

Available in 3 models..

Model	Batrake 8	Batrake 10	Batrake 12
Working width (cm)	500 - 560 cm	560 - 660 cm	600 - 740 cm
Weight (kg)	680 kg	780 kg	890 kg
No Raking Wheels	8	10	12
Power required (HP)	30 HP	30 HP	30 HP

If you are viewing this brochure electronically, you can go directly to demo videos on our website here:

View the Enorossi Sickle Bar Mower demo video here

Design and/or specifications are subject to change without prior notification.