MOUNTED TYPE TURBO ATOMIZER





SMTA-400

111111



Soilmaster reserves the right to make changes in the product and product features.





GENERAL FEATURES

It has polyethylene depot and membrane pumps, which are operated by power take-off from tractor conveys pressuring chemical liquid to nozzles on fan. Fan is also operated with power- take off and it sends pressured air out. Pressured chemical liquid is sprayed by adjustable nozzles around the fan by air circulation. Atomization is provided on right or left sides by remote control.

TECHNICAL DETAILS

CODE	CAPACITY (Liter)	MATERIAL OF Depot	TYPE OF Machine	DIAMATER DF FAN	NUMBER OF NOZZLE	NUMBER OF Diaphragm Piston	FLOW RATE (L/MIN.)	PRESSURE (Bar)	Power of Pump	oil type For pump	OIL CAPACITY For Pump	PTO ROTATION (RPM)	REQUIRED TRACTOR POWER
SMTA-400	400	PLASTIC	BELT-SEPARATOR	60 CM	8	3	71	45	5,5 KW	20w50	0,95 L	540	50 HP
SMTA-400	400	PLASTIC	BELT-SEPARATOR	75 CM	10	4	96	50	7,5 KW	20w50	1,1 L	540	50 HP
SMTA-600	600	PLASTIC	BELT-SEPARATOR	60 CM	8	3	71	45	5,5 KW	20w50	0,95 L	540	50 HP
SMTA-600	600	PLASTIC	BELT-SEPARATOR	75 CM	10	4	96	50	7,5 KW	20w50	1,1 L	540	50 HP
SMTA-800	800	PLASTIC	BELT-SEPARATOR	60 CM	8	3	71	45	5,5 KW	20w50	0,95 L	540	50 HP
SMTA-800	800	PLASTIC	BELT-SEPARATOR	75 CM	10	4	96	50	7,5 KW	20w50	1,1 L	540	50 HP





